

Voyager 1450g

Upgradeable Area-Imaging Scanner

Across many industries, 2D barcoding is the standard. Not only is it possible to hold much more data in a 2D code, but government regulations and supplier mandates are requiring their adoption. Enterprises are also looking to leverage emerging trends that require area-imaging technology – today or in the near future – without the need to purchase additional scanning hardware, or settle for reduced scanning performance.

The Voyager™ 1450g scanner allows enterprises to embrace areaimaging at their own pace, and in the most cost-effective manner.

Built on the durable platform of Honeywell's world-renowned

Voyager series handheld scanners, the Voyager 1450g scanner
delivers omnidirectional reading of linear barcodes, plus the ability to affordably upgrade the device to enable PDF and 2D barcode scanning – either at the time of purchase, or as data capture needs evolve.

For those who only need the ability to read linear and 2D barcodes, the Voyager 1450g scanner is the perfect fit. It doesn't include additional area-imaging features such as advanced image capture and processing applications, allowing Honeywell to keep costs down while offering aggressive linear and 2D scanning at an attractive price.

The Voyager 1450g scanner offers an exceptional value for enterprises that require the versatility of area-imaging technology today or may need it in the future. Produced by a company with decades of experience in engineering-quality data capture solutions, the Honeywell Voyager 1450g area-imaging scanner is a durable and scalable investment.



The Voyager 1450g scanner provides omnidirectional reading of linear barcodes, with the ability to affordably upgrade to PDF and 2D barcode scanning at your convenience.

FEATURES & BENEFITS



Offers omnidirectional reading of virtually all linear barcodes and the most widely used 2D barcodes, including poor-quality and mobile barcodes (2D decoding available in select models).



Scans coupons, mobile tickets, and digital wallets from the screens of mobile devices.



Delivers affordable scanning of 2D barcodes, allowing enterprises to meet their current and future barcode scanning needs with a single device.



Meets diverse scanning requirements by offering models with basic functionality, with flexible software licenses enabling additional functionality as needs evolve.

Voyager 1450g Technical Specifications

MECHANICAL

Dimensions (L x W x H): 62 mm x 169 mm x 82 mm

(2.4 in x 6.6 in x 3.2 in) **Weight:** 130 g (4.6 oz)

ELECTRICAL

Input Voltage: 4.0V DC to 5.5V DC Operating Power: 2 W (400 mA @ 5V DC) Standby Power: 0.45 W (90 mA @ 5V DC) Host System Interface: USB, Keyboard Wedge,

RS-232, IBM 46xx (RS485)

ENVIRONMENTAL

Operating Temperature: 0°C to 40°C

(32°F to 104°F)

Storage Temperature: -40°C to 60°C

(-40°F to 140°F)

 $\textbf{Humidity:} \ \mathsf{Up} \ \mathsf{to} \ 95\% \ \mathsf{relative} \ \mathsf{humidity},$

non-condensing

Drop: Designed to withstand 30 1.5 m (5 ft)

drops to concrete

Tumble: Designed to withstand 1,000 tumbles

from 0.5 m (1.64 ft)

Environmental Sealing: IP40

Light Levels: 0 to 100,000 lux (9,290 foot-candles)

SCAN PERFORMANCE

Scan Pattern: Area Image (640 x 480 pixel array)

Motion Tolerance: Up to 10 cm/s (4 in/s) for 13 mil
UPC at optimal focus

Scan Angle:

Horizontal: 37.8° Vertical: 28.9°

Symbol Contrast: 35% minimum

reflectance difference Pitch, Skew: ±60°, ±70° Decode Capability:

1450g1D: All standard 1D symbologies

1450gPDF: All standard 1D and

PDF417 symbologies

1450g2D: All standard 1D, PDF417,

and 2D symbologies

Warranty: 5-year factory warranty

TYPICAL PERFORMANCE*	EXTENDED RANGE (ER)
NARROW WIDTH	
5 mil Code 39	45 mm – 107 mm (1.8 in – 4.2 in)
13 mil UPC	37 mm – 260 mm (1.4 in – 10.2 in)
20 mil Code 39	42 mm – 360 mm (1.6 in – 14.2 in)
6.7 mil PDF417	42 mm – 107 mm (1.6 in – 4.2 in)
10 mil DM**	42 mm – 107 mm (1.6 in – 4.2 in)
20 mil QR	32 mm - 210 mm (1.2 in - 8.3 in)

^{*} Performance may be impacted by barcode quality and environmental conditions.

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance.

For a complete listing of all supported barcode symbologies, please visit www.honeywellaidc.com/symbologies.

Voyager is a trademark or registered trademark of Honeywell International Inc. in the United States and/or other countries.

Specifications are subject to change without notice.

For more information

www.honeywellaidc.com

Honeywell Safety and Productivity Solutions

9680 Old Bailes Road Fort Mill, SC 29707 800-582-4263 www.honeywell.com



^{**} Data Matrix (DM).