

Product profile

PW50

Mobile Workboard Printer



- Perfect complement for Intermec CN3, CN3e and CK61 mobile computers
- Convenient, integrated solution simplifies use in both portable and vehicle mount applications
- Optimized for DSD, Home Delivery and Field Service applications
- Integrated DEX communications allows easy connectivity to in-store computer system
- Optional magnetic stripe and smart card readers
- Patented power management maximizes battery life
- High-speed electronics and high-voltage battery deliver fast print speeds
- Standard communications includes Bluetooth® and serial

Designed specifically for use with Intermec CN3, CN3e, and CK61 mobile computers, the PW50 four-inch mobile workboard printer provides a convenient, integrated solution for DSD and field service applications. With its integrated DEX communications, fast print speed, Bluetooth connectivity, and optional integrated smart card and magnetic stripe readers, the PW50 provides everything the mobile worker needs to process transactions quickly and easily.

This integrated solution provides a single convenient bundle that can easily be transported or installed in a vehicle. Custom holders safely secure the handheld computer in the mobile printer, yet allow easy removal for scanning or data entry. Hand straps and shoulder straps are available to simplify moving the equipment between the truck and the point of delivery. Drivers can easily keep batteries charged on both the printer and handheld computer: a single electrical connection through the vehicle mount or 12 volt adapter will charge both devices simultaneously.

The PW50 interfaces seamlessly with Bluetooth-enabled Intermec mobile computers including the CN3, CN3e, and CK61. Bluetooth connectivity allows the print job to be initiated whenever the handheld and printer are within wireless range of each other.

A unique design combines a high-voltage battery, patented techniques for power management, and high speed “desktop” electronics. This enables the PW50 to print the full-width of all pixels simultaneously and achieve best-in-class print speeds.

Patented power management of the robust 4-cell Li-Ion battery enables the PW50 to maintain consistent voltage to the print head for high quality printing, independent of the charge remaining in the battery. Battery capacity is designed to print 2 full rolls of receipts with 10% density text without the need to charge or change the batteries.

With 64MB of on-board Flash memory and the ability to store a full Unicode font, the PW50 gives users the flexibility to easily use multiple languages. In addition, users can improve throughput by storing frequently-used formats and graphics on the printer, eliminating the need to download large files from the mobile computer.

The PW50 combines rubberized bumpers, extra-durable gears, and a fully-integrated radio and antenna, enabling the printer to withstand the bumps and drops common to fast-paced mobile usage.

The PW50 is designed for ease of use. Paper loading, charging, and printing are fast and simple, enabling users to perform their job efficiently.

Physical Characteristics

Height: 180 mm (7.0 in)
Width: 310 mm (12.2 in)
Depth: 80 mm (3.2 in)
Weight: 1688 g (59.5 oz) with battery

Environmental

Operating temperature: -20°C to 50°C (-4°F to 122°F)
Storage temperature: -30°C to 70°C (-22°F to 158°F)
Charging temperature: 0°C to 40°C (32°F to 104°F)
Humidity: 10 to 90% (non-condensing)
Electrostatic Discharge:
Contact Discharge: +/-8kV
Air Discharge: +/-15kV
Sealing: IP20
Drop spec: Survives 1.2 m (4 ft) drops to concrete

Power

Battery: Rechargeable 14.8V Li-Ion, 2200mAh (4 cells); 32.56 watt hours; Battery must be ordered separately.
Recharging: 6 hours maximum
AC Adapter: 50 watts
Voltage Range: 12V +/- 5%

Memory

RAM: 16MB
Flash: 64MB

Standard Communications

RS-232 Serial (115k)
Bluetooth® (Class 1)
DEX / UCS

Optional Features

Magnetic Stripe Reader and Smart Card Reader (EMV level 1 certified)

Print Speed and Resolution

4 IPS (100 mm/s)
203 DPI (8 dots/mm)
Maximum Print Width 108 mm (4.25 in)

Media

Supports receipt media in both top coated and uncoated paper in continuous roll stock only.
Type: Direct thermal fanfold and receipt.
Media width: 111.5 mm (4.4 in)
Media length for fanfold: 25.4 mm (1.0 in) min; 609.6 mm (24 in) max
Media length for receipt: Continuous
Media thickness for receipts: 2 mil (0.05 mm) to 4.4 mil (0.112 mm)
Core ID: 19 mm (0.75 in) standard, 10mm (0.40 in) optional
Capacity: 67.3 mm (2.65 in) max. roll diameter (approximately 200", depending on media thickness)

Note: Print Speed and Environmental performance are specified for typical receipt printing applications with 10% density text.

Software Programming Language

ESC-P command sets (Line Print and EZ Print)

Character Sets

West European Latin No.1 and 9: Danish, Dutch, English, Faeroese, Finnish, French, German, Icelandic, Irish, Italian, Norwegian, Portuguese, Spanish, Swedish
East European Latin No.2: Albanian, Czech, English, German, Hungarian, Polish, Rumanian, Serbo-Croatian, Slovak, Slovene
Cyrillic: Bulgarian, Byelorussian, English, Macedonian, Russian, Serbo-Croatian, Ukrainian
Arabic
Greek
Hebrew
U.S. Standard
Europe multilingual
Code Page requirements for Asian characters

Font types

40 column, normal, bold, 80 column, normal, bold, 132 column, normal, bold

Graphics

Supports user-defined fonts, graphics, formats and layouts, including custom logos

Barcode Symbolologies

1D: Codabar, Code 39, Code 128, Code 128 Subset A-C, EAN-8, EAN-13, EAN-128 Subset C, Interleaved 2 of 5, UPC-A
2D: PDF 417

User Interface

LEDs and two external buttons: Standby (Power), Paper Feed
Four audio status indicators: Error alert, hardware change alert, button press alert and startup alert

Accessories

Hand strap, shoulder strap, vehicle mount, cleaning card, battery, four-bay battery charger, A/C adapter, A/C power cord, truck power cable adapter, truck power cable, forklift power cable, serial cable.

Approvals

North America UL and cUL Listed, UL 60950-1
Europe - GS Licensed, EN 60950-1
Mexico NYCE Certified, NOM 19
Other Countries IEC 60950-1
EMC Approvals
USA FCC Title 47, Part 15, Subpart B, Class B;
Europe EMC Directive (EN55022 Class B + EN55024); CISPR22

Warranty

One year; additional Medallion service packages available

North America

Corporate Headquarters
6001 36th Avenue West
Everett, Washington 98203
Phone: (425) 348-2600
Fax: (425) 355-9551

South America & Mexico

Headquarters Office
Newport Beach, California
Phone: (949) 955-0785
Fax: (949) 756-8782

Europe/Middle East &

Africa Headquarters Office
Reading, United Kingdom
Phone: +44 118 923 0800
Fax: +44 118 923 0801

Asia Pacific

Headquarters Office
Singapore
Phone: +65 6303 2100
Fax: +65 6303 2199

Internet

www.intermec.com
Worldwide Locations:
www.intermec.com/locations

Sales

Toll Free NA: (800) 934-3163
Toll in NA: (425) 348-2726
Freephone ROW: 00 800 4488 8844
Toll ROW: +44 134 435 0296

OEM Sales

Phone: (425) 348-2762

Media Sales

Phone: (513) 874-5882

Customer Service and Support

Toll Free NA: (800) 755-5505
Toll in NA: (425) 356-1799

Copyright © 2008 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611880-01A 04/08

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

