SPEC SHEET

SRP-330III

3-inch Thermal POS Printer



Print Characteristics
Print Method
Direct Thermal
Print Speed
Up to 250 mm/sec
Print Resolution
SRP-330III: 180 dpi
SRP-332III: 203 dpi
Print Width
Up to 72 mm
Sensor
Paper End, Cover Open

Media Characteristics
Media Type
Receipt
Media Width
80 mm
Optional 58 mm using 2-inch Partition
Media Roll Diameter
Up to 83 mm
Media Thickness
0.05 to 0.08 mm
Supply Method
Easy Paper Loading

Physical Characteristics
Dimensions (W x L x H)
145 x 195 x 146 mm (5.72 x 7.79 x 5.74 inch)
Weight
1.6 kg (3.52 lbs.)
Electrical
EnergyStar® Certified,
External Power Adapter 100-240 VAC,
50/60 Hz
Drawer Port
2 ports (Via Y-Type Adapter)

Performance Characteristics
Memory
128 MB SDRAM, 64 MB Flash
NV Image Memory
768 Kbytes (Mono)
Receive Buffer
4 Kbytes
User Define Buffer
12 Kbytes
Interface
① USB 2.0 FS + Ethernet + Serial
② USB 2.0 FS + Serial
③ USB 2.0 FS + Parallel
④ USB 2.0 FS + Dual Serial (KOR Only)

Environment Characteristics
Temperature
Operating: 0 to 40°C (32 to 104°F)
Storage: -20 to 60°C (-4 to 140°F)
Humidity
Operating: 10 to 80% RH
Storage: 10 to 90% RH

Software
Emulation
BXL/POS™
Driver/Utility
Windows® Driver, OPOS/JPOS Driver,
Linux®/macOS® CUPS Driver,
Virtual COM USB/Ethernet Driver,
Utility Program, Network Auto Installer
Developer Tools
Android™/iOS®/Windows SDK, Linux SDK,
Xamarin SDK,
Web Print SDK (Android/iOS/Windows/macOS),
Cordova Plugin, MAUI SDK, Flutter™ Plugin
React Native SDK
Design & Print
mPrint App (Android/iOS)

Fonts/Graphics/Symbologies
Character Size
Font A: 12 x 24, Font B: 9 x 17,
Font C: 9 x 24, KOR, CHN, JPN: 24 x 24
Characters per Line
SRP-330III: Font A: 42, Font B, C: 56,
KOR, CHN, JPN: 21
SRP-332III: Font A: 48, Font B, C: 64,
KOR, CHN, JPN: 24
Character Sets
Alphanumeric: 95
Extended Graphics: 128 x 35 page
International: 32
Barcode Symbologies
1D: Coda Bar, Code39, Code93,
Code128, EAN-8, EAN-13, ITF, UPC-A,
UPC-E
2D: Data Matrix, PDF417, QR Code

Accessories/Supplies
Included in the Box
Paper, Cable Cover, AC/DC Adapter,
Power Cord, 2-inch Partition (58 mm),
USB A-B Cable 1.8 m
Options & Accessories
External Buzzer, B-Melodist,
Serial Cable (9-9/25-9 pin),
Parallel Cable

BIXOLON
www.BIXOLON.com

BIXOLON Co.,Ltd.
+82 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Mexico
+521 55 8852 7880
marcelo@bixolonmx.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

BIXOLON MEA
+971 4 222 6480
Russell@bixolon.com

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

March 2026