

# XT5-40

4 inch Thermal Transfer Industrial Label Printer



Retail



Warehouse



Logistics



Manufacturing

# Premium Performance



Standard Auto cutter Peeler Rewinder + Peeler



## Powerful and Robust Design

- Aluminium body and special anti-adhesive coated metal case
- Space-saving design with double folding door
- 3.5 inch full color TFT LCD
- Various options: Auto cutter, Peeler, Rewinder, Rewinder + Peeler

## Best-in-class User Convenience

- Printing speed up to 14 ips (356 mm/sec)
- Fully compatible with market-leading programming languages
- SoftAP - Simple Wi-Fi set up to a mobile device
- Smart Connection™ mobile app – Easy switching from SoftAP to Infrastructure mode
- The industry's fastest Ethernet (1Gbit/sec) embedded
- Twin function™ - Copy printer settings and data via USB storage
- 203, 300 or 600 dpi resolution options
- Clear error display with videos available via a QR code

## Superior Installation and Maintenance

- Various media width supported by a flexible media guide
- Easy installation of media and ribbon
- Toolless maintenance of roller and print head
- Adjustable printer head pressure from 1 to 5 steps
- XPM™, BIXOLON's web-based profile manager (Optional)



**BIXOLON**  
a Better Solution for your Business™

# XT5-40

## 4 inch Thermal Transfer Industrial Label Printer

### Specifications

#### Printer Specifications

**Print Method**

Thermal Transfer, Direct Thermal

**Print Speed**

XT5-40: Up to 14 ips (356 mm/sec)

XT5-43: Up to 10 ips (254 mm/sec)

XT5-46: Up to 5 ips (127 mm/sec)

**Print Resolution**

XT5-40: 203 dpi

XT5-43: 300dpi

XT5-46: 600dpi

**Print Width**

XT5-40: 104mm

XT5-43: 105.7mm

XT5-46: 105.6mm

**Print Length**

XT5-40: Up to 4,000 mm

XT5-43: Up to 2,500 mm

XT5-46: Up to 1,000 mm

**Sensor**

Transmissive(Adjustable),

Reflective (Adjustable), Ribbon-End,

Head open

#### Media Characteristics

**Media Type**

Gap, Black Mark, Notch, Continuous,  
Fan-Fold

**Media Width**

25 ~ 114 mm

**Media Roll Diameter**

Up to 203 mm

**Media Thickness**

0.06 ~ 0.30 mm

**Supply Method**

Easy Paper Loading

**Inner Core**

38.1 ~ 76.2mm, 25.4mm (option)

#### Ribbon Characteristics

**Ribbon Type**

Wax, Wax/Resin, Resin, Outside, inside

**Ribbon Width**

50 ~ 110 mm

**Ribbon Length**

Up to 450 m

**Core Inner Diameter**

25.4 mm

#### Physical Characteristics

**Dimensions (WxDxH)**

STD: 269 x 490 x 324 mm  
(10.59 x 19.29 x 12.76 inch)

Rewinder: 269 x 490 x 407 mm  
(10.59 x 19.29 x 16.02 inch)

**Weight**

STD: 13.98Kg (30.82 lbs.)

Rewinder: 17.98Kg (39.64 lbs.)

**Electrical**

EnergyStar Certified,

Internal Power Adaptor 100-120V/200-240V AC,  
50/60Hz

**Display**

3.5 inch HVGA (262K Colors) TFT LCD

#### Performance Characteristics

**Memory**

512 MB SDRAM, 512 MB Flash

**Interface****Standard:**

USB + Serial + Ethernet<sup>1</sup> + 2 USB Host ports

**Optional:**

- ① USB + Serial + Parallel + Ethernet<sup>1</sup> +  
2 USB Host ports
- ② USB + WLAN<sup>2</sup> + Ethernet<sup>1</sup> + 2 USB Host ports
- ③ USB + WLAN<sup>2</sup> + Parallel + Ethernet<sup>1</sup> +  
2 USB Host ports
- ④ USB + Bluetooth<sup>3</sup> + Ethernet<sup>1</sup> +  
2 USB Host ports + WLAN<sup>3</sup>
- ⑤ USB + Bluetooth<sup>3</sup> + Parallel + Ethernet<sup>1</sup> +  
2 USB Host ports + WLAN<sup>3</sup>

Ethernet<sup>1</sup>: 10/100/1000Mbps (1Gbps)

WLAN<sup>2</sup>: Built-in type, 802.11a/b/g/n

WLAN<sup>3</sup>: USB dongle type, 802.11a/b/g/n  
(Optional)

Bluetooth<sup>3</sup>: Built-in type, MFi iAP2 certified

**Real Time Clock**

Supported

#### Environment Characteristics

**Temperature**

Operating: 5 ~ 40°C (41 ~ 104°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

**Humidity**

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

#### Software

**Emulation**

SLCS™, BPL-Z™ (ZPLII), BPL-E™ (EPL),  
BPL-D™ (DPL)

**Driver / Utility**

Windows Driver (Europlus / Seagull),

Linux / Mac CUPS Driver,

Virtual COM USB / Ethernet Driver,

Utility Program, OPOS / JPOS Driver,

Bartender Ultralite for BIXOLON,

Label Artist-II™, SAP® Device Driver

**SDK / Plugin**

Android / iOS / Windows SDK, Linux SDK,

Chrome SDK, Xamarin SDK

**Application**

Label Artist™ Mobile (Android, iOS),

mPrint App (iOS),

mPrint Server (Windows, iOS)

**MDM (Optional)**

BIXOLON Profile Manager

- XPM™, XCM™ (Windows, Android)

#### Fonts / Graphics / Symbologies

**Fonts**

Bitmap Fonts (SLCS™, BPL-Z, BPL-E) /

Scalable Fonts (SLCS™, BPL-Z) /

Unicode supported (UTF-8, UTF-16LE,

UTF-16BE)

**Graphics**

Supporting user-defined fonts, graphics,

formats and logos

**Barcode Symbologies**

1D: Codabar, Code 11, Code 39, Code 93,

Code 128, EAN-13, EAN-8, Industrial 2-of-5,

Interleaved 2-of-5, Logmars, MSI, Plessey,

Postnet, GS1 DataBar (RSS-14),

Standard 2-of-5, UPC/EAN extensions,

UPC-A, UPC-E, IMB

2D: Aztec, Codablock, Code 49, Data Matrix,

MaxiCode, MicroPDF417, PDF417, QR code,

TLC 39

#### Accessories

**Optional**

Peeler, Auto Cutter, Rewinder,

1" I.D. Core media supply hanger