ZEBRA

SUGGESTED APPLICATIONS

Product identification



Compliance labeling



Work-in-process

Food labeling

FEATURES

· Direct thermal, smooth, paper label with a permanent acrylic adhesive


Z-Perform 2000D

- Good print quality up to 8 in/sec
- Meets FDA 175.105 for indirect food contact requirements
- Limited resistance to moisture or abrasion
- Available in white (65791RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth coated direct thermal paper	3.0 mil
Adhesive	All-temp, acrylic-based	0.5 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
	TOTAL ± 10%	6.0 mil

ADHESIVE STRENGTH



^{*}Attraction between adhesive and surface is so great that the facestock rips.

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
-40° F	-65° F to 131° F	72° F (22° C)
(-40° C)	(-54° C to 55° C)	at 50% RH

Expected Exterior Life

Not recommended for outdoor use

CHEMICAL RESISTANCE

	Chemical	Direct Thermal
Weak	Blood	NR
	Body Fluid	NR
	Salt Water	
	Water	
	Window Cleaner	NR
Moderate	Alcohol	NR
	Ammonia	NR
	Bleach	NR
	IPA	NR
Harsh	Gasoline	NR
	Grease	NR
	Oil	NR
Extreme	Acetone	NR
	IR Reflow	NR
	MEK	NR
	TCE	NR
	Xylene	NR

Recommended
Test in Your Application NR Not Recommended

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies