

ZEBRA

Z-Select 4000D Removable


FEATURES

- Direct thermal, premium, ultra smooth, paper label with a removable acrylic adhesive
- Excellent print quality
- Good scratch/smear resistance
- · Not to be used in applications using chemicals
- · Topcoating is suitable for fanfolding
- Meets FDA 175.105 for indirect food contact requirements
- Available in white (65945RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White smooth topcoated direct thermal paper	3.3 mil
Adhesive	Removable, acrylic- based	0.8 mil
Liner	40 lb. semi-bleached, kraft stock	2.4 mil
	TOTAL ± 10%	6.5 mil

ADHESIVE STRENGTH



TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
40° F (4° C)	-65° F to 140° F (-54° C to 60° C)	72° F (22° C) at 50% RH

Expected Exterior Life

Not recommended for outdoor use

CHEMICAL RESISTANCE

	Chemical	Direct Thermal
~	Blood	
	Body Fluid	
Weak	Salt Water	
_	Water	
	Window Cleaner	
a	Alcohol	NR
Moderate	Ammonia	NR
Jod	Bleach	NR
_	IPA	NR
_	Gasoline	NR
Harsh	Grease	NR
I	Oil	NR
Extreme	Acetone	NR
	IR Reflow	NR
	MEK	NR
	TCE	NR
	Xylene	NR

Recommended ● Test in Your Application NR Not Recommended

SUGGESTED APPLICATIONS

Labeling of packaging materials



Work in process



Food labeling



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies